

CLIC Slide Nut M6 / M8

1. Product Description

- Slide nut to be used with CLIC products $\varnothing 8$ - $\varnothing 59$
- For mounting CLIC to threaded rods, indoors and outdoors

| Slidenut | Item.-Nr. | Thread | Material |
|-----------------------|-----------|--------|------------------------|
| Clic Slide Nut M6 zvp | A88130 | M6 | Steel galvanized |
| Clic Slide Nut M6 A4 | A88240 | M6 | 1.4401 stainless steel |
| Clic Slide Nut M8 zvp | A88285 | M8 | Steel galvanized |
| Clic Slide Nut M8 A4 | A88286 | M8 | 1.4401 stainless steel |

2. Features

- Special nut designed to fix metric rods to Clic Clamps
- Stable due to metal material
- Halogen and phosphorus free
- Length – Width – Height 20x10x2 mm



3. Material Data

| | |
|------------------------|--------------------------------------|
| Material | Steel |
| Tensile strength | >460 N/mm ² |
| Temperature resistance | - 80 °C to + 250 °C |
| Flammability | A1, Non flammable (EN 13501-1 :2009) |
| Halogen | free |

4. Chemical Resistance

| | |
|-------------------------|-----------------------------------|
| Petrol, diesel, oil | resistant |
| Corrosion | 1.4401 outdoor, galvanized Indoor |
| UV resistance | resistant |
| Resistant to weathering | 1.4401 (A4) |

5. fire load according to UL94

Non flammable, no contribution to fire load

6. Conformity

REACH, RoHS

7. Safety Data Sheet

Not applicable

8. Brand

EFCO Befestigungstechnik AG
Grabenstrasse 1 • 8606 Nänikon • Schweiz

cllic[®] CLIC is a registered international trademark of EFCO and is 100% produced in Switzerland

9. Accessories

Further accessories for distance mounting, multiple fastenings etc. can be found on the CLIC-Website.

10. Links/Downloads

For more information, see:

EFCO-Website/EFCO-Shop <http://www.efco.swiss>

The information is based on our current technical knowledge and is intended as a guide. The chemical resistance must be clarified in individual cases on the basis of your own tests.

For further technical information, please contact EFCO